

## FOR USE

ALL FIRE ALARM SYSTEMS UL/NFPA



**DUCUMENTATION**

**DATASHEET**

## FEATURES

- Low current consumption, so with 24VDC/2A control panel it can connect with up to 10 of CL-208 or 100
- Enlarged indicating lamp.
- Individual revert switch.
- Parallel type wiring.
- Build-in FLASH light, higher lumination and longer operating life.

## DESCRIPTION

- This unit is designed to ensure that alarm signal can be actually transmitted to all locations in order to prevent any missing signal caused by separated zones. Especially for the closed room, any fire condition happened can be transmitted to outside for pre-fire alarm notification.
- Use for collidoor and front room
  - Hotel
  - Hospital

## SPECIFICATIONS

| Model.                        | A | FPE.CL-208                           |
|-------------------------------|---|--------------------------------------|
| Alarm Current                 |   | 10-16 mA(LED 2 pcs)                  |
| Stanby Current                |   | 24V DC                               |
| Ambient Temperature           |   | -10 ℃ - +55 ℃                        |
| Material<br>Dimensions(HxWxD) |   | Fire-proof plastic<br>85mmx85mmx24mm |
| Power Source                  |   | 24V DC                               |
| Weight                        |   | about 140g                           |
| Colour                        |   | white surface/ Red lamp cover        |



# FIRE PROTECTION EQUIPMENT CO.,LTD

357/32 Moo4 Klongsongtunnun,  
Ladkrabang, Bangkok 10520

Tel:02-906-9141-3  
Fax:02-906-9144

E-mail:fpe11@hotmail.com  
www.fpethailand.com

UPDATE 4/2007