FIRE ALARM SYSTEM



คุณสมบัติ

- LED โชว์ค้างขณะอลาร์ม เพื่อให้สามารถทราบ จดเกิดเหต
- มีฝาครอบ ป้องกันการกดเล่น ทำจากพลาสติกใส
- มีกุญแจเปิดฝา เพื่อทำการทดสอบได้

CONVENTIONAL DETECTION

EM921 SERIES MANAUL CALL POINTS WITH LED

A modern stylish EM921 Manual Call Point designed to provide greater aesthetic appeal. A low profile surface mounting MCP blends in with today's modern architectural styles. The EM921 MCP is ideal where emergency situations are identified and require an immediate evacuation.

The EM921 range offers improved features for both the end user and the installer. A single maintenance tool provides access to test, reset and release the lid to change the glass or reset the element. The EM921 is fully compatible with all conventional systems available on the market. The new MCP is EN54 compliant, and it is currently undergoing certification at LPCB laboratories in the UK.

Approvals







(4) (€ VdS CNS EN-54





ELECTRICAL SPECIFICATION

Cable Termination: 0.5 - 1.5 mm

Maximum Voltage : 35 VDC

O Current Rating (switch only): 2Amps

ENVIRONMENTAL SPECIFICATION

O Humidity: 0 - 95 % non-condensing

Operating Temperature : -10° c to $+55^{\circ}$ c

Storage Temperature : -10° c to $+55^{\circ}$ c